

KELLY DUPLEX

Machinery Photographs Gauges used in molasses pumping systems



The meter illustrated above is the standard meter used most commonly in molasses applications. Pressure indication is 0-100 PSI.

The meter illustrated below is mated with a **protective diaphragm** which protects the meter mechanism from the effects of molasses and other measured materials. The diaphragm is filled with glycerin, then the meter is calibrated before shipment. The diaphragm provides extra life and improved accuracy to the meter.



THE DUPLEX MILL & MANUFACTURING CO.
415 SIGLER ST., P.O. BOX 1266, SPRINGFIELD, OH 45501-1266 USA
Email: eww@dmmc.com Home Page: <http://www.dmmc.com>

TEL: 937/325-5555
FAX: 937/325-0859

FAX: 937/325-2229

IMPORTANT: All illustrations and specifications are subject to change without notice and any drawing dimensions may not be to scale. Machines shown with protective covers, guards, grates, maintenance panels or interlocking limit switches removed are for illustrative purposes only. All protective devices must be in place before power is connected to machine and before operation. All sales are subject to our prevailing terms and General Conditions of Sale. See DMMC #1281-9.
SAFETY IS EVERYONE'S BUSINESS! Safe operations are profitable operations. Write or phone today for your free copy of our publication #369: **KELLY DUPLEX PROCESSING MACHINERY HAZARD WARNINGS.**